

View Online at <https://aerobasegroup.com/nsn/4730-00-727-9787>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

121.1 degrees fahrenheit single response

**Connection Style:**

Flareless (tube) 1st end

**Leg Length:**

1.450 inches 2nd end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Material:**

Steel comp 1213 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1214

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-c-16232, ty m, cl 1 military specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

1 tube coupling nut w/sleeve and 1 preformed packing

**Specification Data:**

96906-ms51839 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

27a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-c-16232 spec.