

View Online at <https://aerobasegroup.com/nsn/4730-00-727-9795>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

121.0 degrees celsius single response

**End Application:**

23n ship, ohio class ssn (trident)

**Connection Style:**

Flareless (tube) 1st end

**Leg Length:**

0.891 inches 1st end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.438 inches all ends

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Special Features:**

Supports 1025-01-126-6648; howitzer, med. Towed 155-mm, m198

**Material:**

Steel comp 304 or steel comp 316 or steel comp 303

**Material Specification:**

Qq-s-763 federal specification single material response or qq-s-763 federal specification single material response or qq-s-764 federal specification single material response

**Media For Which Designed:**

Hydraulic fluid 1st response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 2 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

1 tube coupling nut w/sleeve and 1 preformed packing

**Specification Data:**

96906-ms51839 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

27a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.