

View Online at <https://aerobasegroup.com/nsn/4730-00-731-6740>

Thread Class:

2a 1st end

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

Mrap rg-33 auv; mrap buffalo mk2a2

Connection Style:

Plain (pipe) 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.750 inches 1st end

Nominallength:

2.062 inches

Material:

Stainless steel

Material Specification:

66, 300 series federal standard single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 1 or 2 federal specification single treatment response

Thread Series Designator:

Un 1st end

Furnished Items And Quantity:

1 tube coupling nut w/sleeve

Specification Data:

81349-mil-f-18866 government specification and 96906-ms51500 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.