

View Online at <https://aerobasegroup.com/nsn/4730-00-739-0593>

Body Style:

Relieved

Concentric Hole Depth:

3.560 inches

Concentric Hole Diameter:

0.182 inches

Overall Length:

4.065 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

1.064 inches

First End Thread Length:

0.500 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

0.748 inches

Second Diameter From Wrenching Feature:

0.102 inches

Third Diameter From Wrenching Feature:

0.097 inches

Fourth Diameter From Wrenching Feature:

Any acceptable

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

2.950 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

Any acceptable

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

2.950 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

Any acceptable

First Radial Fluid Hole Diameter:

3.102 inches

Second Radial Fluid Hole Diameter:

0.102 inches

Distance From First Radial Hole Center To End Of Bolt:

2.332 inches

Distance From Second Radial Hole Center To End Of Bolt:

0.610 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

3.690 inches

Wrenching Feature Height:

0.375 inches

Min. Tensile Strength (psi):

46550 pounds per square inch

First End Thread Series Designator:

Unf

First End Thread Size:

0.500 inches

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0