

View Online at <https://aerobasegroup.com/nsn/4730-00-756-2290>

**Body Style:**

Plain

**Head Diameter:**

1.250 inches

**Concentric Hole Depth:**

2.500 inches

**Concentric Hole Diameter:**

0.343 inches

**Overall Length:**

5.250 inches

**First End Connection Type:**

Threaded external tube

**First End Thread Class:**

2a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal pipe

**Second End Style Designator:**

Plain

**Second End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

0.203 inches

**First End Thread Length:**

1.250 inches

**Wrenching Feature Style:**

Round

**Distance From Bolt End To Hole Center:**

0.312 inches

**First Diameter From Wrenching Feature:**

Between 0.885 inches and 0.888 inches

**Second Diameter From Wrenching Feature:**

Between 0.873 inches and 0.874 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

0.625 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:**

3.500 inches

**First Radial Fluid Hole Diameter:**

0.125 inches

**Distance From First Radial Hole Center To End Of Bolt:**

2.875 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

4.750 inches

**Wrenching Feature Height:**

0.500 inches

**Hardness Rating:**

Between 40.0 rockwell c and 50.0 rockwell c

**First End Thready Qty Per Inch (tpi):**

14

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

0.875 inches

**Second End Thread Series Designator:**

Npt

**Special Features:**

32 microinches aa surface finish of body 0.031 in. Circular pitch of straight knurl

**Material:**

Steel comp 1045

**Material Specification:**

Qq-s-633 federal specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A121a0