NSN 4730-00-767-2208

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-767-2208

Thread Class:

3a first fluid end connection

Overall Length:

Between 2.994 inches and 3.328 inches

Second Leg Length:

0.657 inches

Quick Disconnect Method:

Spring push-lock all ends

Quick Disconnect Size:

0.906 inches all ends

Maximum Operating Temp:

54.0 degrees celsius single response

Connection Style:

Flared first fluid end connection

Leg Length:

0.657 inches

Connection Type:

Threaded external tube first fluid end connection

Features Provided:

Self-sealing

Second End Relationship With First End:

Identical

Maximum Operating Pressure And Media For Which Designed:

1000.0 pounds per square inch any acceptable

Maximum Operating Pressure:

1000.0 pounds per square inch single response

Thread Size:

0.750 inches first fluid end connection

Seat Angle:

37.0 degrees

Maximum Operating Tempurature And Media For Which Designed:

Err-070

Outside Diameter Tube Accommodated:

0.500 inches first fluid end connection

Material:

Aluminum alloy

Surface Treatment:

Anodize

Style Designator:

Coupling assembly

Thread Series Designator:

Unf first fluid end connection

NSN 4730-00-767-2208

Quick Disconnect Coupling Assembly - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531s0