## NSN 4730-00-767-2208

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-767-2208

**Thread Class:** 

3a first fluid end connection

**Overall Length:** 

Between 2.994 inches and 3.328 inches

Second Leg Length:

0.657 inches

**Quick Disconnect Method:** 

Spring push-lock all ends

**Quick Disconnect Size:** 

0.906 inches all ends

**Maximum Operating Temp:** 

54.0 degrees celsius single response

**Connection Style:** 

Flared first fluid end connection

Leg Length:

0.657 inches

**Connection Type:** 

Threaded external tube first fluid end connection

**Features Provided:** 

Self-sealing

Second End Relationship With First End:

Identical

Maximum Operating Pressure And Media For Which Designed:

1000.0 pounds per square inch any acceptable

**Maximum Operating Pressure:** 

1000.0 pounds per square inch single response

Thread Size:

0.750 inches first fluid end connection

Seat Angle:

37.0 degrees

Maximum Operating Tempurature And Media For Which Designed:

Err-070

**Outside Diameter Tube Accommodated:** 

0.500 inches first fluid end connection

Material:

Aluminum alloy

**Surface Treatment:** 

Anodize

**Style Designator:** 

Coupling assembly

**Thread Series Designator:** 

Unf first fluid end connection

## NSN 4730-00-767-2208

Quick Disconnect Coupling Assembly - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A531s0