## NSN 4730-00-770-3483

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-770-3483

Body Style:	
Plain	
Concentric I	-
	20 inches and 1.180 inches
	Hole Diameter:
	62 inches and 1.182 inches
Overall Leng	-
Between 1.83	34 inches and 1.854 inches
	yle Designator:
Flared	
First End Th	read Class:
3a	
First End Th	read Direction:
Right-hand	
Cotter Pin H	ole Diameter:
Between 0.04	46 inches and 0.056 inches
Width Acros	s Flats:
0.688 inches	
First End Th	read Length:
Between 0.31	18 inches and 0.344 inches
Wrenching F	Feature Style:
Hexagon	
Distance Fro	om Bolt End To Hole Center:
Between 1.71	16 inches and 1.756 inches
First Diamet	er From Wrenching Feature:
Between 0.43	30 inches and 0.432 inches
Length From	n Bearing Surface Of Wrenching Feature To End Of First Diameter:
Between 1.24	47 inches and 1.252 inches
First Radial	Fluid Hole Diameter:
Between 0.16	62 inches and 0.182 inches
Distance Fro	om First Radial Hole Center To End Of Bolt:
Between 1.02	21 inches and 1.041 inches
Length From	n Bearing Surface Of Wrenching Feature To Bolt End:
Between 1.64	46 inches and 1.666 inches
Wrenching F	Feature Height:
Between 0.14	43 inches and 0.203 inches
Min. Tensile	Strength (psi):
10000 pound	ls per square inch
First End Th	ready Qty Per Inch (tpi):
20	
First End Th	read Series Designator:
Unf	

## NSN 4730-00-770-3483

Fluid Passage Bolt - Page 2 of 2

First End Seat Angle:

45.0 degrees

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A121a0

