NSN 4730-00-776-4630

Fluid Flow Restrictor Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-776-4630 **Body Material:** Aluminum alloy **Thread Class:** 3a second connection **Thread Direction:** Right-hand second connection **Overall Length:** 2.452 inches **Thread Size Designator:** 9/16-18 second connection **Packing Material:** Rubber, synthetic **Filter Material:** Steel, corrosion resisting **Operating Tempurature Range:** -65.0 to 275.0 degrees fahrenheit **Orifice Diameter:** 0.050 inches **Compression Type:** Double compression second connection **Design Type:** Straight Width Across Flats: 0.813 inches **End Connection Type:** Threaded male, compression first connection **End Connection Similarity:** Not identical **Pressure Rating:** 3000.0 pounds per square inch **Thread Series:** Unf or nf second connection **Strainer Type And Quantity:** 2 filter Valve Size: 0.812 inches **End Connection Component Type And Size For Which Designed:** 1/4 in. Od tube and 3/8 in. Od tube Flow Rate And Fluid Type: 4.0 gallons per minute oil

Surface Treatment: Anodized

NSN 4730-00-776-4630

Fluid Flow Restrictor Unit - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

Т359-с