

View Online at <https://aerobasegroup.com/nsn/4730-00-776-9842>

**Concentric Hole Depth:**

1.250 inches

**Concentric Hole Diameter:**

0.216 inches

**Overall Length:**

2.520 inches

**First End Connection Type:**

Threaded external tube

**First End Style Designator:**

Plain

**First End Thread Class:**

3a

**First End Thread Direction:**

Right-hand

**Second End Connection Type:**

Threaded internal boss

**Second End Style Designator:**

Gasket seal

**Second End Thread Class:**

2b

**Second End Thread Direction:**

Right-hand

**Cotter Pin Hole Diameter:**

0.125 inches

**Width Across Flats:**

0.875 inches

**First End Thread Length:**

0.750 inches

**Second End Thread Length:**

0.500 inches

**Wrenching Feature Style:**

Hexagon

**Distance From Bolt End To Hole Center:**

0.218 inches

**First Diameter From Wrenching Feature:**

0.562 inches

**Second Diameter From Wrenching Feature:**

0.476 inches

**Third Diameter From Wrenching Feature:**

0.562 inches

**Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:**

0.510 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:**

0.630 inches

**Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:**

1.250 inches

**First Radial Fluid Hole Diameter:**

0.094 inches

**Distance From First Radial Hole Center To End Of Bolt:**

1.390 inches

**Length From Bearing Surface Of Wrenching Feature To Bolt End:**

1.960 inches

**Wrenching Feature Height:**

0.500 inches

**First End Thread Series Designator:**

Unf

**First End Thread Size:**

0.562 inches

**Second End Thread Size:**

0.250 inches

**Second End Thread Series Designator:**

Unf

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 cond military standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A121a0

**Mil-std (military Standard):**

Mil-s-5626 spec.