## NSN 4730-00-797-7386

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-797-7386 **Thread Class:** 2a first fluid end connection **Overall Length:** 4.608 inches Second End Style Designator (non-core): Err-090 **Second End Thread Class:** 2b Second Leg Length: 0.625 inches **Quick Disconnect Method:** Twist-lock all ends **Second Fluid End Connection Type:** Threaded internal boss **Maximum Operating Temp:** 85.0 degrees celsius single response **Connection Style:** Flared first fluid end connection Leg Length: 0.718 inches **Connection Type:** Threaded internal boss second fluid end connection Second End Relationship With First End: Not identical **Maximum Operating Pressure And Media For Which Designed:** 3000.0 pounds per square inch any acceptable **Maximum Operating Pressure:** 3000.0 pounds per square inch single response Thread Size: 0.750 inches second fluid end connection **Mounting Flange Location:** First leg Seat Angle: 37.0 degrees Second End Thread Size: 0.750 inches **Second End Thread Series Designator:** Unf

Maximum Operating Tempurature And Media For Which Designed:

85.0 degrees celsius any acceptable

**Outside Diameter Tube Accommodated:** 

0.500 inches first fluid end connection

## NSN 4730-00-797-7386

Quick Disconnect Coupling Assembly - Page 2 of 2



Material:
Copper alloy
Style Designator:
Coupling assembly
Thread Series Designator:
Unf second fluid end connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A531s0