NSN 4730-00-798-2966

Tube Tee - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-798-2966

| View Online at https://aerobasegroup.com/nsn/4730-00-798-296 |
|-----------------------------------------------------------------|
| Thread Class: |
| 2a all ends |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit single response |
| Connection Style: |
| Flared (tube) all ends |
| Leg Length: |
| 1.812 inches all ends |
| Connection Type: |
| Threaded external tube all ends |
| Thready Qty Per Inch (tpi): |
| 12 all ends |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 1.312 inches all ends |
| Seat Angle: |
| 37.0 degrees all ends |
| Outside Diameter Tube Accommodated: |
| 1.000 inches all ends |
| Material: |
| Stainless steel |
| Material Specification: |
| 66, 300 series federal standard single material response |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35, type 2 federal specification single treatment response |
| Thread Series Designator: |
| Un all ends |
| Furnished Items And Quantity: |
| 2 short coupling nut with sleeve |
| Specification Data: |
| 81343-j514 professional/industrial association standard |
| Specification Or Standard: |
| 12a figure |
| Shelf Life: |
| N/a |
| |

--

Unit Of Measure:

NSN 4730-00-798-2966

Tube Tee - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.