

View Online at <https://aerobasegroup.com/nsn/4730-00-800-1517>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit 2nd response

**Connection Style:**

Flareless (tube) 1st end

**Leg Length:**

0.980 inches 1st end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch 2nd response

**Thread Size:**

0.750 inches all ends

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

45.0 degrees

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Material:**

Steel comp 12114

**Material Specification:**

Fed-std-66 federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232, class 1 military specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

1 locknut and 1 tube coupling nut w/sleeve and 1 flat washer

**Specification Data:**

81343-j514 professional/industrial association standard 96906-ms51842 government standard and

**Specification Or Standard:**

27b figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-p-16232 spec.