# NSN 4730-00-800-1956

Tube Reducer - Page 1 of 2





#### **Thread Class:**

2a all ends

## **Reducer Type:**

Concentric

## Maximum Operating Temp:

121.0 degrees celsius single response

## **Connection Style:**

Flareless (tube) all ends

#### **Connection Type:**

Threaded external tube all ends

## Thready Qty Per Inch (tpi):

12 all ends

## Maximum Operating Pressure:

3000.0 pounds per square inch single response

#### **Thread Size:**

1.875 inches 1st end

## Seat Angle:

12.0 degrees all ends

## **Outside Diameter Tube Accommodated:**

1.500 inches 1st end

## Nominallength:

1.750 inches

## Material:

Steel

## Surface Treatment:

Phosphate

## Surface Treatment Specification:

Mil-c-16232 military specification single treatment response outside

## **Thread Series Designator:**

Un all ends

## **Specification Data:**

81343-j514 professional/industrial association standard

## **Specification Or Standard:**

20 figure

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A080b0

# NSN 4730-00-800-1956

Tube Reducer - Page 2 of 2

## Mil-std (military Standard):

Mil-c-16232 spec.

