## NSN 4730-00-800-1962

Tube Reducer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-800-1962 **Thread Class:** 2a 2nd end **Reducer Type:** Concentric **Maximum Operating Temp:** 250.0 degrees fahrenheit 1st response **Connection Style:** Flareless (tube) all ends **Connection Type:** Threaded external tube all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end Seat Angle: 12.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Nominallength: 1.219 inches Material: Steel comp 304 or steel comp 316 **Material Specification:** 66, aisi 304/sae 30304 federal standard 1st material response or 66, aisi/sae 300 series federal standard 2nd material response Media For Which Designed: Hydraulic fluid 1st response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 federal specification 1st treatment response or astm a380 assn standard 2nd treatment response **Thread Series Designator:** Unf all ends **Specification Data:** 96906-ms51895 government standard **Specification Or Standard:** 20 figure Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 4730-00-800-1962

Tube Reducer - Page 2 of 2



Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.