Tube Fitting Clinch Sleeve - Page 1 of 1



Casehardenig Indicator:CasehardenedOverall Length:0.372 inchesMetallic Hardness Rating:99.5 rockwell bFlange Width:0.109 inchesFlange Outside Diameter:0.625 inchesSeat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter:0.500 inchesHose/tube Outside Diameter:0.500 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesHaterial:1 Steel, federal standard 66, comp 12/14 or steel, federal standard 66, comp 1010Surface Treatment:Phosphate manganeseSyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:96906-ms51825 government standard and 81343-j514 professional/industrial association standard
Overall Length:0.372 inchesMetalic Hardness Rating:99.5 rockwell bFlange Width:0.109 inchesFlange Outside Diameter:0.625 inchesSeat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesSteel, federal standard 66, comp 12/14 or steel, federal standard 66, comp 12/14 or steel, federal standard 66, comp 12/14 or steel comp 10/10Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:FlarelessSurface Treatment:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
0.372 inchesMetallic Hardness Rating:99.5 rockwell bFlange Width:0.109 inchesFlange Outside Diameter:0.625 inchesSeat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesMaterial:Steel, federal standard 66, comp 12114 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12114 or steel comp 1010Surface Treatment:Phosphate manganeseSurface Treatment:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
Metallic Hardness Rating:99.5 rockwell bFlange Width:0.109 inchesFlange Outside Diameter:0.625 inchesSeat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesMaterial:Steel, federal standard 66, comp 12114 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12114 or steel comp 1010Surface Treatment:Phosphate manganeseSurface Treatment:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
99.5 rockwell b Flange Width: 0.109 inches Flange Outside Diameter: 0.625 inches Seat Angle In Deg: 40.000 Sleeve Outside Diameter: 0.589 inches Hose/tube Outside Diameter For Which Designed: 0.500 inches Material: 0.500 inches Material: Steel, federal standard 66, comp 12114 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12114 or steel comp 1010 Material: Steel, federal standard 66, comp 12114 or steel comp 1010 Material: Steel, federal standard 66, comp 12114 or steel comp 1010 Surface Treatment: Phosphate manganese Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Flange Width:0.109 inchesFlange Outside Diameter:0.625 inchesSeat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesBaterial:Steel, federal standard 66, comp 12114 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12114 or steel comp 1010Burface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
0.109 inches Flange Outside Diameter: 0.625 inches Seat Angle In Deg: 40.000 Sleeve Outside Diameter: 0.589 inches Hose/tube Outside Diameter For Which Designed: 0.500 inches Material: Steel, federal standard 66, comp 12114 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12114 or steel comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Flange Outside Diameter:0.625 inchesSeat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesMaterial:Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12l14 or steel comp 1010Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, maip-c-16232, type 1-canceledSpecification Data:
0.625 inches Seat Angle In Deg: 40.000 Sleeve Outside Diameter: 0.589 inches Hose/tube Outside Diameter For Which Designed: 0.500 inches Material: 0.500 inches Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Seat Angle In Deg:40.000Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesMaterial:0.500 inchesSteel, federal standard 66, comp 12114 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12114 or steel comp 1010Burface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
40.000 Sleeve Outside Diameter: 0.589 inches Hose/tube Outside Diameter For Which Designed: 0.500 inches Material: 0.500 inches Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12l14 or steel comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Sleeve Outside Diameter:0.589 inchesHose/tube Outside Diameter For Which Designed:0.500 inchesMaterial:Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12l14 or steel comp 1010Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
0.589 inches Hose/tube Outside Diameter For Which Designed: 0.500 inches Material: Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12l14 or steel comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Hose/tube Outside Diameter For Which Designed:0.500 inchesMaterial:Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12l14 or steel comp 1010Steel, federal standard 66, comp 12l14 or steel comp 1010Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
0.500 inches Material: Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12l14 or steel comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Material:Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010Material:Steel, federal standard 66, comp 12l14 or steel comp 1010Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
Steel, federal standard 66, comp 12l14 or steel, federal standard 66, comp 1010 Material: Steel, federal standard 66, comp 12l14 or steel comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Material:Steel, federal standard 66, comp 12l14 or steel comp 1010Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
Steel, federal standard 66, comp 12l14 or steel comp 1010 Surface Treatment: Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Surface Treatment:Phosphate manganeseStyle Designator:FlarelessSurface Treatment:Phosphate, mil-c-16232, type 1-canceledSpecification Data:
Phosphate manganese Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Style Designator: Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Flareless Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Surface Treatment: Phosphate, mil-c-16232, type 1-canceled Specification Data:
Phosphate, mil-c-16232, type 1-canceled Specification Data:
Specification Data:
·
96906-ms51825 government standard and 81343-i514 professional/industrial association standard
······································
Specification Or Standard:
28 figure
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т385-ј