

View Online at <https://aerobasegroup.com/nsn/4730-00-801-6663>

Thread Class:

2a all ends

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

Ukm tank, combat, ft, 120mm gun (m1a1)

Connection Style:

Flareless (tube) 2nd end

Leg Length:

0.891 inches 2nd end

Connection Type:

Threaded external tube 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Seat Angle:

12.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.250 inches 2nd end

Material:

Stainless steel

Material Specification:

Fed-std-66, 300 series federal standard single material response

Media For Which Designed:

Hydraulic fluid 2nd response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type1 or 2 federal specification single treatment response

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

2 tube coupling nut w/sleeve and 1 preformed packing

Specification Data:

96906-ms51841 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

26d figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.