

View Online at <https://aerobasegroup.com/nsn/4730-00-802-7050>

Thread Class:

2a all ends

Maximum Operating Temp:

121.0 degrees celsius single response

Connection Style:

Flareless (tube) all ends

Connection Type:

Threaded external tube all ends

Thready Qty Per Inch (tpi):

12 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.312 inches 1st end bulkhead

Seat Angle:

12.0 degrees all ends

Outside Diameter Tube Accommodated:

1.000 inches all ends

Nominallength:

2.719 inches

Material:

Steel

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-c-16232, type m, class 1 military specification single treatment response

Style Designator:

Flareless w/ bulkhead threads

Thread Series Designator:

Un 1st end bulkhead

Furnished Items And Quantity:

2 short coupling nut and 2 compression sleeve

Specification Data:

81343-j514 professional/industrial association standard

Specification Or Standard:

25c figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-c-16232 spec.