## NSN 4730-00-803-1680

Fluid Pressure Line Multiple Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-803-1680 **Thread Class:** За **Thread Direction:** Right-hand **Overall Length:** Between 1.625 inches and 1.844 inches **Overall Width:** 0.813 inches Thickness: 0.750 inches **Thread Size:** 7/16 in.-20 **Thread Provision:** Threaded **Connection Style:** Flared **Bolt Hole Diameter:** 0.438 inches Seat Angle In Deg: 37.0 **Screw Thread Series Designator:** Unf Seat: Included **Deg Between Outlets:** 45.0 Fluid Connection Quantity: Fluid Conveyance Type And Size For Which Designed: 1/4 in. Od tube **Bolt Hole Flats Serrations:** Provided **Bolt Hole Fluid Passage:** Provided Material: Steel, federal standard 66, comp 304 or steel, federal standard 66, comp 316 Material: Steel comp 304 or steel comp 316 **Surface Treatment:** Passivate or passivate

Style Designator:
1 fluid connection

## NSN 4730-00-803-1680

Fluid Pressure Line Multiple Connector - Page 2 of 2



Surface Treatment:
Passivated, qq-p-35 or passivated, qq-p-35, type 2
Specification Data:
81343-as4875/1 professional/industrial association standard and 88044-an778 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-f-5509 spec.

T385-g