NSN 4730-00-803-5776

Pipe To Tube Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-803-5776

View Online at https://aerobasegroup.com/nsn/4730-00-803-5776
Thread Class:
2a 1st end
Maximum Operating Temp:
121.0 degrees fahrenheit single response
End Application:
Supports harnischfeger corp, model m32012, crane truck mounted
Connection Style:
Inverted flare (tube) 2nd end
Connection Type:
Threaded external tube 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Criticality Code Justification:
Feat
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Nominallength:
1.240 inches
Special Features:
Weapon system essential
Material:
Steel
Media For Which Designed:
Hydraulic fluid single response
Surface Treatment Specification:
J514 assn standard single treatment response and qq-p-416, type 1, cl 2 federal specification single treatment response
Thread Series Designator:
Unf 1st end
Furnished Items And Quantity:
1 flared sleeve and 1 short coupling nut
Specification Data:
81349-mil-f-18866 government specification and 96906-ms51500 government standard
Specification Or Standard:
5a figure
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4730-00-803-5776

Pipe To Tube Straight Adapter - Page 2 of 2



Demi			

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-18866 spec.