
# NSN 4730-00-805-5100

Tube Reducer - Page 1 of 2





#### **Thread Class:**

3a all ends

#### **Reducer Type:**

Concentric

## Maximum Operating Temp:

225.0 degrees fahrenheit single response

#### **Connection Style:**

Flared (tube) all ends

#### **Connection Type:**

Threaded external tube all ends

### Thready Qty Per Inch (tpi):

12 1st end

#### Thread Size:

1.062 inches 1st end

#### Seat Angle:

## 37.0 degrees all ends

### **Criticality Code Justification:**

Feat

## **Outside Diameter Tube Accommodated:**

0.750 inches 1st end

#### Nominallength:

2.000 inches

### **Special Features:**

Supports grumman a10a aircraft; weapon system essential

#### Material:

Aluminum alloy 2014 or aluminum alloy 2024

### **Material Specification:**

Qq-a-225/4, t6 federal specification 1st material response or qq-a-225/6, t6 federal specification 2nd material response

### Media For Which Designed:

Hydraulic fluid single response

### Surface Treatment:

Anodize

### Surface Treatment Specification:

Mil-a-8625, type 2, cl 2 military specification single treatment response

### Thread Series Designator:

Unjf 2nd end

## **Specification Data:**

96906-ms24399 government standard and 81349-mil-f-5509 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 4730-00-805-5100

Tube Reducer - Page 2 of 2

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.

