

View Online at <https://aerobasegroup.com/nsn/4730-00-812-0882>

**Thread Class:**

3a all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit 1st response

**Connection Style:**

Flared w/ gasket seal (boss) all ends

**Leg Length:**

0.953 inches all ends

**Connection Type:**

Threaded external boss all ends

**Thready Qty Per Inch (tpi):**

12 all ends

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

3.000 inches all ends

**Nominallength:**

2.875 inches

**Material:**

Steel comp 12L14 or steel comp 1010

**Material Specification:**

66, carbon steel, 0.20 percent maximum federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 1st response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification 1st treatment response or mil-c-81562, type 2 military specification 2nd treatment response

**Style Designator:**

Flared w/ center wrenching facility

**Thread Series Designator:**

Unj all ends

**Furnished Items And Quantity:**

2 preformed packing

**Specification Data:**

96906-ms24392 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-c-81562 spec.