NSN 4730-00-814-2247

Tube Elbow - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-814-2247

Thread Class: 3a all ends Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style: Flared (tube) all ends Leg Length: 2.531 inches 1st end and 2.594 inches 1st end Connection Type: 7.571 inches 1st end and 2.594 inches 1st end Connection Type: 7.572 inches all ends 2.594 inches 1st end Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment: Cadmium and paint
Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style: Flared (tube) all ends Leg Length: 2.531 inches 1st end and 2.594 inches 1st end Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
250.0 degrees fahrenheit single response Connection Style: Flared (tube) all ends Leg Length: 2.531 inches 1st end and 2.594 inches 1st end Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Connection Style: Flared (tube) all ends Leg Length: 2.531 inches 1st end and 2.594 inches 1st end Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Flared (tube) all ends Leg Length: 2.531 inches 1st end and 2.594 inches 1st end Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Leg Length: 2.531 inches 1st end and 2.594 inches 1st end Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
 2.531 inches 1st end and 2.594 inches 1st end Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Connection Type: Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Threaded external tube 2nd end bulkhead Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Thread Size: 0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
0.562 inches all ends Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Seat Angle: 37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
37.0 degrees all ends Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Flow Angle: 90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
90.0 degrees Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Outside Diameter Tube Accommodated: 0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
0.375 inches all ends Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Material: Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Steel Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Media For Which Designed: Hydraulic fluid 2nd response Surface Treatment:
Hydraulic fluid 2nd response Surface Treatment:
Surface Treatment:
Cadmium and paint
Thread Series Designator:
Unjf 1st end bulkhead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A080b0