## NSN 4730-00-814-9977

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-814-9977

| Body Style  | e   |
|-------------|---|
| Plain       |   |
| Concentric  | Hole Depth:   |
| 2.141 inche | S   |
| Concentric  | Hole Diameter:  |
| 0.172 inche | S   |
| Overall Ler | ngth:   |
| 2.634 inche | S   |
| First End T | hread Class:  |
| 3a          |   |
| First End T | Thread Direction:   |
| Right-hand  |   |
| Width Acro  | oss Flats:  |
| 0.687 inche | s   |
| First End T | Thread Length:  |
| 0.406 inche | s   |
| Wrenching   | Feature Style:  |
| Hexagon     |   |
| First Diame | eter From Wrenching Feature:                                      |
| 0.435 inche | s   |
| Length Fro  | om Bearing Surface Of Wrenching Feature To End Of First Diameter: |
| 2.040 inche | s   |
| First Radia | I Fluid Hole Diameter:  |
| 0.172 inche | is  |
| Distance Fi | rom First Radial Hole Center To End Of Bolt:                      |
| 2.055 inche | is  |
| Length Fro  | om Bearing Surface Of Wrenching Feature To Bolt End:              |
| 2.446 inche | S   |
| First End T | hready Qty Per Inch (tpi):  |
| 20          |   |
| First End T | hread Series Designator:  |
| Unf         |   |
| First End T | hread Size:   |
| 0.438 inche | S   |
| Material:   |   |
| Steel comp  | 302   |
| Material Sp | pecification:   |
| Mil-s-7720, | cond b military specification single material response            |
| Surface Tre | eatment:  |
| Cadmium     |   |
| Shelf Life: |   |
| N/a         |   |
|             |   |

## NSN 4730-00-814-9977

Fluid Passage Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-s-7720 spec.

