NSN 4730-00-824-5878

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-824-5878

| Body Style: |
|--|
| Plain |
| Concentric Hole Depth: |
| 0.703 inches |
| Concentric Hole Diameter: |
| 0.070 inches |
| Overall Length: |
| 1.406 inches |
| First End Connection Type: |
| Threaded external tube |
| First End Style Designator: |
| Plain |
| First End Thread Class: |
| 3a |
| First End Thread Direction: |
| Right-hand |
| Cotter Pin Hole Diameter: |
| 0.076 inches |
| Width Across Flats: |
| 0.438 inches |
| First End Thread Length: |
| 0.343 inches |
| Wrenching Feature Style: |
| Hexagon |
| Distance From Bolt End To Hole Center: |
| 0.144 inches |
| First Diameter From Wrenching Feature: |
| 0.249 inches |
| Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: |
| 0.838 inches |
| First Radial Fluid Hole Diameter: |
| 0.076 inches |
| Distance From First Radial Hole Center To End Of Bolt: |
| 0.791 inches |
| Length From Bearing Surface Of Wrenching Feature To Bolt End: |
| 1.281 inches |
| First End Thread Series Designator: |
| Unf |
| First End Thread Size: |
| 0.250 inches |
| Special Features: |
| W/nas516-1 fitting |

NSN 4730-00-824-5878

Fluid Passage Bolt - Page 2 of 2



| late | |
|------|--|
| | |

Steel

Surface Treatment:

Cadmium

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0