## NSN 4730-00-826-8163

Fluid Pressure Line Multiple Connector - Page 1 of 2



Trailar resource Entre Manapier Commession in age 7 of E
View Online at https://aerobasegroup.com/nsn/4730-00-826-8163
Thread Class:
3a
Thread Direction:
Right-hand
Overall Length:
Between 2.609 inches and 2.800 inches
Overall Width:
Between 1.350 inches and 1.375 inches
Thickness:
Between 1.350 inches and 1.375 inches
Thread Size:
7/8 in14
Thread Provision:
Threaded
Connection Style:
Flared
Bolt Hole Diameter:
0.875 inches
Seat Angle In Deg:
37.0
Screw Thread Series Designator:
Unf
Seat:
Included
Deg Between Outlets:
45.0
Fluid Connection Quantity:
1
Fluid Conveyance Type And Size For Which Designed:
5/8 in.Od tube
Bolt Hole Flats Serrations:
Not provided
Bolt Hole Fluid Passage:
Provided
Special Features:
Anodized blue
Material:
Aluminum alloy, qq-a-225/4, alloy 2014, t6 or aluminum alloy, qq-a-225/6, alloy 2024, t6
Material:
Aluminum alloy 2014 or aluminum alloy 2024
Surface Treatment:

Anodize

## NSN 4730-00-826-8163

Mil-f-5509 spec.

Fluid Pressure Line Multiple Connector - Page 2 of 2



Style Designator:
1 fluid connection
Surface Treatment:
Anodized, mil-a-8625, type 2, class 2
Specification Data:
81343-as4875/1 professional/industrial association standard and 80205-nas554 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
T385-g
Mil-std (military Standard):