

View Online at <https://aerobasegroup.com/nsn/4730-00-839-0427>

Thread Class:

2a all ends

Maximum Operating Temp:

250.0 degrees fahrenheit 1st response

Connection Style:

Flareless (tube) all ends

Leg Length:

0.891 inches all ends

Connection Type:

Threaded external tube all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches all ends

Seat Angle:

12.0 degrees all ends

Outside Diameter Tube Accommodated:

0.250 inches all ends

Material:

Steel comp 12L14 or steel comp 1010

Material Specification:

66, carbon steel, 0.020 percent maximum federal standard single material response

Media For Which Designed:

Hydraulic fluid 1st response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-c-16232, type m, class 1 military specification single treatment response

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

3 tube coupling nut w/sleeve

Specification Data:

96906-ms51811 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

22b figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-c-16232 spec.