NSN 4730-00-842-1766

Pipe To Tube Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-842-1766 **Thread Class:** 2a 1st end **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** Plain (pipe) 2nd end **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Nominallength: 1.220 inches Material: Stainless steel Media For Which Designed: Hydraulic fluid single response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response inside **Thread Series Designator:** Unf 1st end **Furnished Items And Quantity:** 1 flared sleeve and 1 short coupling nut **Specification Data:** 96906-ms51500 government standard and 81349-mil-f-18866 government specification and 81343-j514 professional/industrial association standard **Specification Or Standard:** 2a figure Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A080b0

NSN 4730-00-842-1766

Pipe To Tube Straight Adapter - Page 2 of 2



Mil-std (military Standard):

Mil-f-18866 spec.