## NSN 4730-00-853-2065

Sediment Strainer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-853-2065

| Wire Diameter:  |
|---|
| 0.0037 inches   |
|   |
| Mesh Size:  |
| 120.0   |
| Tempurature Rating:   |
| 200.0 degrees fahrenheit                                      |
| Features Provided:  |
| Manual shut-off valve   |
| Filtering Media Design:                                       |
| Mesh single filtering media response                          |
| First Intake Connection Type:                                 |
| Threaded external pipe side near top                          |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical   |
| First Discharge Connection Type:                              |
| Threaded internal pipe side near top                          |
| First Intake Thread Series Designator:                        |
| Npt   |
| First Discharge Thread Series Designator:                     |
| Npt   |
| First Intake Thread Size:                                     |
| 0.375 inches  |
| First Discharge Thread Size:                                  |
| 0.125 inches  |
| First Intake Thready Qty Per Inch (tpi):                      |
| 18  |
| First Discharge Thready Qty Per Inch (tpi):                   |
| 27  |
| First Intake Thread Direction:                                |
| Right-hand  |
| First Discharge Thread Direction:                             |
| Right-hand  |
| Material:   |
| Glass body  |
| Media For Which Designed:                                     |
| Air and gas and fuel/oil, hydrocarbon and water               |
| Fsc Application Data:   |
| Fuel system, tractor  |
| Departure From Cited Designator:                              |
| Pne   |
| Shelf Life:   |
| N/a   |
|   |

## NSN 4730-00-853-2065

Sediment Strainer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A24000

