NSN 4730-00-855-0550

Fluid Pressure Line Multiple Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-00-855-0550 |
|--|
| Thread Class: 3a |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| 1.531 inches |
| Overall Width: |
| 0.8125 inches |
| Thickness: |
| 0.750 inches |
| Thread Size: |
| 7/16 in20 |
| Thread Provision: |
| Threaded |
| Connection Style: |
| Flared |
| Bolt Hole Diameter: |
| 0.438 inches |
| Seat Angle In Deg: |
| 37.0 |
| Screw Thread Series Designator: |
| Unf |
| Seat: |
| Included |
| Fluid Connection Quantity: |
| 1 |
| Fluid Conveyance Type And Size For Which Designed: |
| 1/4 in. Od tube |
| Bolt Hole Flats Serrations: |
| Not provided |
| Bolt Hole Fluid Passage: |
| Provided |
| Special Features: |
| Fluid connection end restricted with 0.039 to 0.041 in. Diameter orifice |
| Material: |
| Steel, corrosion resisting |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Style Designator: |

1 fluid connection

NSN 4730-00-855-0550

Fluid Pressure Line Multiple Connector - Page 2 of 2



| Surrace Treatment |
|-------------------|
| Passivated |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

T385-g