## NSN 4730-00-888-4754

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-888-4754

Concentric Hole Diameter:  Between 0.075 inches and 0.076 inches  Overall Length: 0.990 inches  First End Thread Class: 3a  First End Thread Direction: Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches  First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: Between 1.80 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf First End Thread Series Designator:
Overall Length:  0.990 inches  First End Thread Class: 3a  First End Thread Direction: Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches  First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon  Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches  Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches  Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi): 24  First End Thread Series Designator: Unf
0.990 inches  First End Thread Class: 3a  First End Thread Direction: Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
First End Thread Class:  3a  First End Thread Direction: Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
First End Thread Direction: Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
First End Thread Direction: Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
Right-hand Width Across Flats: Between 0.367 inches and 0.376 inches First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
Width Across Flats:  Between 0.367 inches and 0.376 inches  First End Thread Length: 0.175 inches  Wrenching Feature Style:  Hexagon  Second Diameter From Wrenching Feature:  Between 0.168 inches and 0.170 inches  Fourth Diameter From Wrenching Feature:  Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Between 0.367 inches and 0.376 inches  First End Thread Length: 0.175 inches  Wrenching Feature Style: Hexagon  Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches  Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches  Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi): 24  First End Thread Series Designator: Unf
First End Thread Length: 0.175 inches Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
Wrenching Feature Style: Hexagon Second Diameter From Wrenching Feature: Between 0.168 inches and 0.170 inches Fourth Diameter From Wrenching Feature: Between 0.247 inches and 0.248 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: Between 0.220 inches and 0.230 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
Second Diameter From Wrenching Feature:  Between 0.168 inches and 0.170 inches  Fourth Diameter From Wrenching Feature:  Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Second Diameter From Wrenching Feature:  Between 0.168 inches and 0.170 inches  Fourth Diameter From Wrenching Feature:  Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Fourth Diameter From Wrenching Feature:  Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Fourth Diameter From Wrenching Feature:  Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Between 0.247 inches and 0.248 inches  Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:  Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Between 0.220 inches and 0.230 inches  Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches  Hardness Rating: Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi): 24  First End Thread Series Designator: Unf
Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:  0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
0.710 inches  Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:  Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Between 0.055 inches and 0.065 inches  Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi): 24  First End Thread Series Designator: Unf
Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:  0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
0.810 inches  Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Hardness Rating:  Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
Between 18.0 rockwell c and 26.0 rockwell c  First End Thready Qty Per Inch (tpi):  24  First End Thread Series Designator:  Unf
First End Thready Qty Per Inch (tpi): 24 First End Thread Series Designator: Unf
24  First End Thread Series Designator:  Unf
First End Thread Series Designator: Unf
Unf
First End Thread Size.
First End Thread Size:
0.312 inches
Material:
Stainless steel
Stainless steel  Material Specification:
Material Specification:
Material Specification: Ams5613 assn standard single material response

--

## NSN 4730-00-888-4754

Fluid Passage Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A121a0