

View Online at <https://aerobasegroup.com/nsn/4730-00-897-4882>

Thread Class:

3a first fluid end connection

Overall Length:

4.125 inches

Second End Style Designator (non-core):

Err-090

Second End Flange Thickness:

Between 0.060 inches and 0.250 inches

Second End Thread Class:

3b

Second Leg Length:

0.594 inches

Quick Disconnect Method:

Twist-lock all ends

Second Fluid End Connection Type:

Threaded internal boss

Mounting Flange Shape Style (non-core):

Err-090

Mounting Flange Thickness:

0.312 inches

Mounting Flange Length:

2.500 inches

Mounting Flange Width:

1.812 inches

Mounting Flange Bolt Hole Quantity:

4

Mounting Flange Bolt Hole Diameter:

0.193 inches

Err Default:

Err default

Err Default:

Err default

Distance From Mounting Flange To Fluid End:

0.969 inches

Maximum Operating Temp:

67.2 degrees fahrenheit single response

Connection Style:

Flareless first fluid end connection

Leg Length:

0.594 inches

Connection Type:

Threaded external tube first fluid end connection

Features Provided:

Self-sealing

Thready Qty Per Inch (tpi):

12 first fluid end connection

Second End Relationship With First End:

Not identical

Maximum Operating Pressure And Media For Which Designed:

Err-070

Maximum Operating Pressure:

600.0 pounds per square inch 1st response

Thread Size:

1.062 inches first fluid end connection

Mounting Flange Location:

Second leg

Seat Angle:

12.0 degrees

Second End Thready Qty Per Inch (tpi):

12

Second End Thread Size:

1.062 inches

Second End Thread Series Designator:

Un

Maximum Operating Temperature And Media For Which Designed:

Err-070

Outside Diameter Tube Accommodated:

0.375 inches first fluid end connection

Material:

Aluminum alloy

Surface Treatment:

Anodize

Style Designator:

Coupling assembly

Thread Series Designator:

Un first fluid end connection

Specification Data:

96906-ms24334 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531s0