

View Online at <https://aerobasegroup.com/nsn/4730-00-897-4884>

Thread Class:

3a first fluid end connection

Overall Length:

4.543 inches

Second End Style Designator (non-core):

Err-090

Second End Thread Class:

3a

Second Leg Length:

1.781 inches

Quick Disconnect Method:

Twist-lock all ends

Second Fluid End Connection Type:

Threaded internal boss

Maximum Operating Temp:

54.0 degrees fahrenheit single response

Connection Style:

Flareless first fluid end connection

Leg Length:

0.625 inches

Connection Type:

Threaded external tube first fluid end connection

Thready Qty Per Inch (tpi):

12 first fluid end connection

Second End Relationship With First End:

Not identical

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, water base

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

1.313 inches first fluid end connection

Seat Angle:

12.0 degrees

Second End Thread Size:

0.875 inches

Second End Thread Series Designator:

Unjf

Maximum Operating Temperature And Media For Which Designed:

Err-070

Outside Diameter Tube Accommodated:

0.625 inches first fluid end connection

Special Features:

Bulkhead threaded on 2nd end

Material:

Aluminum

Surface Treatment:

Anodize

Style Designator:

Coupling assembly

Thread Series Designator:

Un first fluid end connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531s0

Mil-std (military Standard):

Mil-c-25427 spec.