

View Online at <https://aerobasegroup.com/nsn/4730-00-906-2322>

Thread Class:

3a all ends

Connection Style:

Flared (tube) all ends

Leg Length:

0.531 inches 2nd end

Connection Type:

Threaded external tube all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.500 inches all ends

Seat Angle:

37.0 degrees all ends

Outside Diameter Tube Accommodated:

0.312 inches all ends

Nominallength:

2.047 inches

Special Features:

Supports grumman a10 sircraft

Material:

Aluminum alloy 2014 or aluminum alloy 2024

Material Specification:

Qq-a-225/4, t6 federal specification 1st material response or qq-a-225/6, t6 or t851 federal specification 2nd material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

Style Designator:

Flared w/ bulkhead thread

Thread Series Designator:

Unjf 1st end bulkhead

Specification Data:

96906-ms24393 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-a-8625 spec.