## NSN 4730-00-908-7067

Fluid Pressure Line Multiple Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4730-00-908-7067



| Thread Class:   |
|---|
| 3a  |
| Thread Direction:                                     |
| Right-hand  |
| Overall Length:                                       |
| 1.626 inches  |
| Overall Width:  |
| 0.813 inches  |
| Thickness:  |
| 0.781 inches  |
| Thread Size:  |
| 7/16 in20   |
| Thread Provision:                                     |
| Threaded  |
| Connection Style:                                     |
| Flared  |
| Bolt Hole Diameter:                                   |
| 0.437 inches  |
| Seat Angle In Deg:                                    |
| 37.0  |
| Screw Thread Series Designator:                       |
| Unf   |
| Seat:   |
| Included  |
| Deg Between Outlets:                                  |
| 75.0  |
| Fluid Connection Quantity:                            |
| 1   |
| Fluid Conveyance Type And Size For Which Designed:    |
| 1/4 in. Od tube                                       |
| Bolt Hole Flats Serrations:                           |
| Not provided  |
| Bolt Hole Fluid Passage:                              |
| Provided  |
| Special Features:                                     |
| Different sealing concept than an777; e/i f4 aircraft |
| Material:   |
| Steel   |
| Material:   |
| Steel   |
| Surface Treatment:                                    |
| Cadmium   |

## NSN 4730-00-908-7067

Mil-f-5509 spec.

Fluid Pressure Line Multiple Connector - Page 2 of 2



| Style Designator:   |
|---|
| 1 fluid connection  |
| Surface Treatment:  |
| Cadmium   |
| Specification Data:   |
| 81343-as4875/1 professional/industrial association standard and 80205-nas553 professional/industrial association standard |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| T385-g  |
| Mil-std (military Standard):  |