

View Online at <https://aerobasegroup.com/nsn/4730-00-919-1688>

Body Style:

Shoulder

Head Diameter:

1.000 inches

Distance From Centerline To Flat:

0.430 inches

Concentric Hole Depth:

0.640 inches

Concentric Hole Diameter:

Between 0.093 inches and 0.098 inches

Overall Length:

2.518 inches

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Cotter Pin Hole Diameter:

Between 0.105 inches and 0.110 inches

First End Thread Length:

0.660 inches

Wrenching Feature Style:

Round with wrench flats

Distance From Bolt End To Hole Center:

0.190 inches

First Diameter From Wrenching Feature:

0.624 inches

Second Diameter From Wrenching Feature:

Between 0.436 inches and 0.437 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.753 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

1.733 inches

First Radial Fluid Hole Diameter:

Between 0.061 inches and 0.066 inches

Distance From First Radial Hole Center To End Of Bolt:

2.115 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

2.393 inches

Wrenching Feature Height:

0.125 inches

First End Thready Qty Per Inch (tpi):

20

First End Thread Series Designator:

Unf

First End Thread Size:

0.438 inches

Material:

Steel

Material Specification:

Mil-s-5626, cond c4 military specification single material response

Surface Treatment:

Cadmium

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A121a0

Mil-std (military Standard):

Mil-s-5626 spec.