NSN 4730-00-922-9635

Fluid Pressure Line Multiple Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-00-922-9635 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| 2.686 inches |
| Overall Width: |
| 2.172 inches |
| Thickness: |
| 1.188 inches |
| Thread Size: |
| 7/16 in20 |
| Thread Provision: |
| Threaded |
| Connection Style: |
| Flareless |
| Bolt Hole Diameter: |
| 0.8125 inches |
| Seat Angle In Deg: |
| 12.0 |
| Seat Radius: |
| 12.000 inches |
| Screw Thread Series Designator: |
| Unjf |
| Seat: |
| Included |
| Deg Between Outlets: |
| 90.0 |
| Fluid Connection Quantity: |
| 3 |
| Fluid Conveyance Type And Size For Which Designed: |
| 1/4 in. Od tube |
| Bolt Hole Flats Serrations: |
| Not provided |
| Bolt Hole Fluid Passage: |
| Provided |
| Second Deg Between Outlets: |
| 90.0 |
| Material: |
| Aluminum alloy |

Material:

Aluminum alloy

NSN 4730-00-922-9635

Fluid Pressure Line Multiple Connector - Page 2 of 2



| Surface Treatment: |
|---------------------|
| Anodize |
| Style Designator: |
| 3 fluid connections |
| Surface Treatment: |
| Anodized |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: T385-g