## NSN 4730-00-922-9656

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-922-9656

**Thread Class:** 

3a first fluid end connection

**Overall Length:** 

4.540 inches

Second End Style Designator (non-core):

Err-090

**Second End Thread Class:** 

3b

Second Leg Length:

0.781 inches

**Quick Disconnect Method:** 

Spring push-pull all ends

**Second Fluid End Connection Type:** 

Threaded internal boss

**Maximum Operating Temp:** 

135.0 degrees celsius single response

**Connection Style:** 

Flareless first fluid end connection

Leg Length:

0.625 inches

**Connection Type:** 

Threaded external tube first fluid end connection

**Features Provided:** 

Self-sealing

Second End Relationship With First End:

Not identical

**Maximum Operating Pressure And Media For Which Designed:** 

3000.0 pounds per square inch any acceptable

**Maximum Operating Pressure:** 

3000.0 pounds per square inch single response

**Thread Size:** 

0.875 inches first fluid end connection

Seat Angle:

12.0 degrees

**Second End Thread Size:** 

0.875 inches

**Second End Thread Series Designator:** 

Unf

Maximum Operating Tempurature And Media For Which Designed:

135.0 degrees celsius any acceptable

**Outside Diameter Tube Accommodated:** 

0.625 inches first fluid end connection

## NSN 4730-00-922-9656

Quick Disconnect Coupling Assembly - Page 2 of 2



Material:
Aluminum alloy
Surface Treatment:
Anodize
Style Designator:
Coupling assembly
Thread Series Designator:
Unf first fluid end connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A531s0