## NSN 4730-00-924-2052

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-924-2052

**Thread Class:** 

3a first fluid end connection

**Overall Length:** 

4.696 inches

**Quick Disconnect Method:** 

Quick lead thread all ends

Mounting Flange Shape Style (non-core):

Err-090

**Mounting Flange Outside Diameter:** 

2.750 inches

**Mounting Flange Bolt Hole Quantity:** 

.

**Mounting Flange Bolt Hole Diameter:** 

Between 0.196 inches and 0.201 inches

**Mounting Flange Bolt Circle Diameter:** 

2.375 inches

**Distance From Mounting Flange To Fluid End:** 

1.574 inches

**Maximum Operating Temp:** 

71.1 degrees celsius 1st response

**Connection Style:** 

Flareless first fluid end connection

Leg Length:

1.375 inches

**Connection Type:** 

Threaded external tube first fluid end connection

**Features Provided:** 

Self-sealing

Thready Qty Per Inch (tpi):

12 first fluid end connection

**Second End Relationship With First End:** 

Identical

**Maximum Operating Pressure And Media For Which Designed:** 

1000.0 pounds per square inch any acceptable

**Maximum Operating Pressure:** 

1000.0 pounds per square inch single response

**Thread Size:** 

1.312 inches first fluid end connection

**Mounting Flange Location:** 

First leg

Seat Angle:

12.0 degrees

## NSN 4730-00-924-2052

Quick Disconnect Coupling Assembly - Page 2 of 2



## Maximum Operating Tempurature And Media For Which Designed: Err-070 **Outside Diameter Tube Accommodated:** 1.000 inches first fluid end connection Material: Aluminum alloy **Surface Treatment:** Anodize Style Designator: Coupling assembly **Thread Series Designator:** Un first fluid end connection Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A531s0