

View Online at <https://aerobasegroup.com/nsn/4730-00-931-1983>

**Thread Class:**

3a first fluid end connection

**Overall Length:**

Between 5.141 inches and 5.760 inches

**Second Leg Length:**

0.880 inches

**Quick Disconnect Method:**

Spring push-pull all ends

**Maximum Operating Temp:**

320.0 degrees fahrenheit single response

**Connection Style:**

Flared first fluid end connection

**Leg Length:**

1.447 inches

**Connection Type:**

Threaded external tube first fluid end connection

**Features Provided:**

Self-sealing

**Thready Qty Per Inch (tpi):**

12 first fluid end connection

**Second End Relationship With First End:**

Identical

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch any acceptable

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

1.062 inches first fluid end connection

**Seat Angle:**

45.0 degrees

**Maximum Operating Temperature And Media For Which Designed:**

320.0 degrees fahrenheit any acceptable

**Outside Diameter Tube Accommodated:**

0.750 inches first fluid end connection

**Special Features:**

Bulkhead threads on 1st fluid end connection

**Material:**

Aluminum or aluminum alloy

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Coupling assembly

**Thread Series Designator:**

Un first fluid end connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A531s0

**Mil-std (military Standard):**

Mil-a-8625 spec.