Pipe To Tube Straight Adapter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-958-1111

| Thread Class:  |
|--|
| 2a 1st end   |
| Connection Style:  |
| Plain (pipe) 2nd end   |
| Connection Type:   |
| Threaded external tube 1st end   |
| Thready Qty Per Inch (tpi):  |
| 12 1st end   |
| Maximum Operating Pressure:  |
| 3000.0 pounds per square inch single response                                    |
| Thread Size:   |
| 1.000 inches 2nd end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Outside Diameter Tube Accommodated:  |
| 1.000 inches 1st end   |
| Nominallength:   |
| 2.297 inches   |
| Material:  |
| Stainless steel  |
| Media For Which Designed:  |
| Hydraulic fluid single response  |
| Surface Treatment:   |
| Passivate inside   |
| Surface Treatment Specification:   |
| Qq-p-35, type 2 federal specification single treatment response inside           |
| Thread Series Designator:  |
| Un 1st end   |
| Furnished Items And Quantity:  |
| 1 flared sleeve and 1 short coupling nut   |
| Specification Data:  |
| 96906-ms51500 government standard and 81349-mil-f-18866 government specification |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A080b0   |
| Mil-std (military Standard):   |
| Mil-f-18866 spec.  |
|  |