NSN 4730-00-966-6470

Fluid Passage Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-966-6470

Body Style: Relieved **Concentric Hole Depth:** Between 1.780 inches and 1.840 inches Concentric Hole Diameter: Between 0.249 inches and 0.255 inches **Overall Length:** 2.150 inches **First End Connection Type:** Threaded external tube First End Style Designator: Plain First End Thread Class: За **First End Thread Direction:** Right-hand Width Across Flats: Between 0.744 inches and 0.756 inches First End Thread Length: 0.347 inches Wrenching Feature Style: Hexagon First Diameter From Wrenching Feature: Between 0.608 inches and 0.611 inches **Second Diameter From Wrenching Feature:** Between 0.370 inches and 0.390 inches **Third Diameter From Wrenching Feature:** Between 0.608 inches and 0.611 inches **Fourth Diameter From Wrenching Feature:** Between 0.435 inches and 0.437 inches Length From Bearing Surface Of Wrenching Feature To End Of First Diameter: 0.197 inches Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter: 0.700 inches Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter: 0.760 inches Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter: 0.903 inches First Radial Fluid Hole Diameter: Between 0.097 inches and 0.101 inches

1.320 inches

Distance From First Radial Hole Center To End Of Bolt:

NSN 4730-00-966-6470

Fluid Passage Bolt - Page 2 of 2



Length From Bearing Surface Of Wrenching Feature To Bolt End:
Between 1.860 inches and 1.880 inches
Wrenching Feature Height:
Between 0.260 inches and 0.300 inches
First End Thread Series Designator:
Unf
First End Thread Size:
0.562 inches
Special Features:
W/six lockwire holes in head
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-325 t6 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 type 1 military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A121a0
Mil-std (military Standard):

Mil-a-8625 spec.