NSN 4730-00-969-6652

Swivel Flange To Hose Elbow - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-969-6652	
Bolt Hole Quantity:	
4 1st end	
Maximum Operating Temp:	
125.0 degrees fahrenheit single response	
Connection Style:	
Gripping nipple (nose) 2nd end	
Leg Length:	
0.475 inches 1st end	
Width:	
1.390 inches 1st end	
Length:	
1.390 inches 1st end	
Flange Shape:	
Rectangular with holes 1st end	
Connection Type:	
Threaded external hose gripping 2nd end	
Maximum Operating Pressure:	
1500.0 pounds per square inch single response	
Flow Angle:	
45.0 degrees	
Thickness:	
0.234 inches 1st end	
Bolt Hole Diameter:	
0.205 inches 1st end	
Center To Center Distance Between Bolt Holes Along Length:	
0.950 inches 1st end	
Center To Center Distance Between Bolt Holes Along Width:	
0.950 inches 1st end	
Flange Face Design:	
Raised swivel 1st end	
Raised Face Height:	
0.020 inches 1st end	
Raised Face Diameter:	
0.875 inches 1st end	
Inside Diameter Hose Accommodated:	
0.340 inches 2nd end	
Outside Diameter Hose Accommodated:	
0.500 inches 2nd end	
Material:	

Steel comp 321 shoulder

Material Specification:

Mil-t-8808 federal specification 1st material response elbow

NSN 4730-00-969-6652

Mil-f-27272 spec.

Swivel Flange To Hose Elbow - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-27272 military specification single treatment response outside
Specification Data:
96906-ms27066 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A080b0
Mil-std (military Standard):