## NSN 4730-00-969-6653

Swivel Flange To Hose Elbow - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-969-6653 **Thread Class:** 3a 2nd end **Bolt Hole Quantity:** 4 1st end **Maximum Operating Temp:** 610.0 degrees fahrenheit single response **Connection Style:** Swivel, plain (hose) 2nd end Leg Length: 2.063 inches 2nd end Width: 1.750 inches 1st end Length: 1.750 inches 1st end Flange Shape: Rectangular with holes 1st end **Connection Type:** Threaded external hose 2nd end **Maximum Operating Pressure:** 1250.0 pounds per square inch 2nd response **Thread Size:** 1.375 inches 2nd end Flow Angle: 45.0 degrees Thickness: 0.234 inches 1st end **Bolt Hole Diameter:** 0.205 inches 1st end Center To Center Distance Between Bolt Holes Along Length: 1.312 inches 1st end Center To Center Distance Between Bolt Holes Along Width: 1.312 inches 1st end Flange Face Design: Raised swivel 1st end **Raised Face Height:** 0.020 inches 1st end **Raised Face Diameter:** 1.500 inches 1st end Material: Steel comp 321 shoulder

**Material Specification:** 

Qq-s-763 federal specification single material response union

## NSN 4730-00-969-6653

Swivel Flange To Hose Elbow - Page 2 of 2



Media For Which Designed:
Fuel 1st response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-27272 military specification single treatment response
Thread Series Designator:
Unef 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A080b0
Mil-std (military Standard):

Mil-t-8808 spec.