

View Online at <https://aerobasegroup.com/nsn/4730-00-969-6655>

**Bolt Hole Quantity:**

4 1st end

**Maximum Operating Temp:**

232.0 degrees celsius single response

**Connection Style:**

Gripping nipple (nose) 2nd end

**Leg Length:**

0.769 inches 1st end

**Width:**

1.390 inches 1st end

**Length:**

1.390 inches 1st end

**Flange Shape:**

Rectangular with holes 1st end

**Connection Type:**

Threaded external hose gripping 2nd end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Flow Angle:**

90.0 degrees

**Thickness:**

0.234 inches 1st end

**Bolt Hole Diameter:**

0.205 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

0.950 inches 1st end

**Center To Center Distance Between Bolt Holes Along Width:**

0.950 inches 1st end

**Flange Face Design:**

Raised swivel 1st end

**Raised Face Height:**

0.020 inches 1st end

**Raised Face Diameter:**

0.875 inches 1st end

**Inside Diameter Hose Accommodated:**

0.426 inches 2nd end

**Outside Diameter Hose Accommodated:**

0.616 inches 2nd end

**Material:**

Steel comp 321 shoulder

**Material Specification:**

Qq-s-763 cond a federal specification single material response shoulder

**Media For Which Designed:**

Fuel 2nd response

**Surface Treatment:**

Passivate outside

**Surface Treatment Specification:**

Mil-f-27272 military specification single treatment response outside

**Specification Data:**

96906-ms27066 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-t-8808 spec.