

View Online at <https://aerobasegroup.com/nsn/4730-00-969-6656>

Bolt Hole Quantity:

4 1st end

Maximum Operating Temp:

443.5 degrees fahrenheit single response

Connection Style:

Gripping nipple (nose) 2nd end

Leg Length:

1.965 inches 2nd end

Width:

1.468 inches 1st end

Length:

1.468 inches 1st end

Flange Shape:

Rectangular with holes 1st end

Connection Type:

Threaded external hose gripping 2nd end

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Flow Angle:

90.0 degrees

Thickness:

0.234 inches 1st end

Bolt Hole Diameter:

0.205 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.038 inches 1st end

Center To Center Distance Between Bolt Holes Along Width:

1.038 inches 1st end

Flange Face Design:

Raised swivel 1st end

Raised Face Height:

0.020 inches 1st end

Raised Face Diameter:

1.000 inches 1st end

Inside Diameter Hose Accommodated:

0.562 inches 2nd end

Outside Diameter Hose Accommodated:

0.706 inches 2nd end

Material:

Steel comp 321 shoulder

Material Specification:

Qq-s-763 cond a federal specification single material response shoulder

Media For Which Designed:

Fuel 1st response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-27272 military specification single treatment response

Specification Data:

96906-ms27066 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-t-8808 spec.