

View Online at <https://aerobasegroup.com/nsn/4730-00-979-5891>

Thread Class:

2a center bulkhead

Maximum Operating Temp:

250.0 degrees fahrenheit single response

Connection Style:

Flared w/ gasket seal (boss) 2nd end

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.875 inches center bulkhead

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Nominallength:

2.740 inches

Material:

Steel comp 12L14

Material Specification:

66 assn standard single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment Specification:

J514 assn standard single treatment response and mil-c-81562, type 1, cl 3 military specification single treatment response

Thread Series Designator:

Unf center bulkhead

Furnished Items And Quantity:

2 tube coupling nut w/sleeve and 1 preformed packing and 1 bulkhead nut

Specification Data:

96906-ms51520 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

3a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-c-81562 spec.