

View Online at <https://aerobasegroup.com/nsn/4730-00-979-5891>

**Thread Class:**

2a center bulkhead

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**Connection Style:**

Flared w/ gasket seal (boss) 2nd end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.875 inches center bulkhead

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.625 inches 1st end

**Nominallength:**

2.740 inches

**Material:**

Steel comp 12L14

**Material Specification:**

66 assn standard single material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment Specification:**

J514 assn standard single treatment response and mil-c-81562, type 1, cl 3 military specification single treatment response

**Thread Series Designator:**

Unf center bulkhead

**Furnished Items And Quantity:**

2 tube coupling nut w/sleeve and 1 preformed packing and 1 bulkhead nut

**Specification Data:**

96906-ms51520 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

3a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-c-81562 spec.