

View Online at <https://aerobasegroup.com/nsn/4730-00-986-7531>

Thread Class:

3a first fluid end connection

Overall Length:

2.381 inches

Second End Style Designator (non-core):

Err-090

Second End Outside Diameter Tube Accommodated:

0.125 inches

Second End Thread Class:

3a

Second Leg Length:

0.375 inches

Quick Disconnect Method:

Push-pull all ends

Second Fluid End Connection Type:

Threaded external tube

Maximum Operating Temp:

60.0 degrees celsius single response

Connection Style:

Flared first fluid end connection

Leg Length:

0.656 inches

Connection Type:

Threaded external tube first fluid end connection

Features Provided:

Safety locking feature and self-sealing

Second End Relationship With First End:

Not identical

Maximum Operating Pressure And Media For Which Designed:

750.0 pounds per square inch any acceptable

Maximum Operating Pressure:

750.0 pounds per square inch single response

Thread Size:

0.312 inches first fluid end connection

Seat Angle:

37.0 degrees

Second End Seat Angle:

12.0 degrees

Second End Thread Size:

0.312 inches

Second End Thread Series Designator:

Unjf

Maximum Operating Temperature And Media For Which Designed:

60.0 degrees celsius any acceptable

Outside Diameter Tube Accommodated:

0.125 inches first fluid end connection

Material:

Aluminum alloy

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Coupling assembly

Thread Series Designator:

Unjf first fluid end connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531s0

Mil-std (military Standard):

Mil-a-8625 spec.