

View Online at <https://aerobasegroup.com/nsn/4730-00-993-7085>

Quick Disconnect Method:

Cam-locking all ends

Bolt Hole Quantity:

8

Basic Shape Style:

Round first quick disconnect end

Connection Style:

Plain first quick disconnect end

Leg Length:

5.000 inches second quick disconnect end

Connection Type:

Unthreaded internal tube third quick disconnect end

Maximum Operating Pressure:

200.0 pounds per square inch single response

Flow Angle:

120.0 degrees

Outside Diameter:

6.625 inches

Thickness:

0.375 inches

Bolt Hole Diameter:

0.437 inches

Bolt Circle Diameter:

5.875 inches

Material Specification:

Qq-a-601, t5 federal specification single material response

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification single treatment response

Style Designator:

Wye

Test Data Document:

81349-mil-c-27487 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

14 type and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531y0

Mil-std (military Standard):

Mil-a-8625 spec.